



ARMADI - CASSEFORTI E CASSETTE IGNIFUGHE



Gli armadi ignifughi sono realizzati con corpo a doppia parete di lamiera di acciaio, all'interno del quale viene inserito lo speciale isolante antincendio "STYRONITE F", resistente alle altissime temperature sviluppate durante gli incendi. Gli armadi ignifughi della serie DATA-SAFE hanno al loro interno una struttura aggiuntiva, protetta da una porta con guarnizioni a tenuta stagna, contro la diffusione dei gas, che permette di mantenere la temperatura interna al di sotto dei 50 gradi, in modo da preservare i supporti magnetici dal calore prodotto dall'incendio.



The fire proof cabinets have a body with a double wall made of steel plate a special fire resistant insulator, "STYRONITE F" inserted inside this body, is resistant to the extremely high temperatures that develop during a fire. The fire proof cabinets of the range DATA-SAFE have an additional structure inside, protected by a door with hermetic seal, against gas diffusion, allowing the internal temperature to be kept below 50 degrees, This protects the magnetic medium from the heat produced by the fire.



Tutti gli armadi ignifughi sono certificati secondo i severi standard di collaudo dello Swedish National Testing and Research Institute, ottenendo le varie omologazioni e sono prodotti da azienda certificata ISO 9001.

All the fire proof cabinets are certified in accordance to the strict testing standards of the Swedish National Testing and Research Institute, obtaining the various approvals and are produced by a company certified ISO 9001.

ARMADI IGNIFUGHI FIRE PROOF CABINETS



Fire resistance tested and certified 60P, 90P, 120P under fire NT FIRE 017 by SP Swedish National Testing and Research Institute.



CASSEFORTI IGNIFUGHE FIRE PROOF SAFES



CERTIFICATA / CERTIFIED
EN 15659-LFS 30P



CERTIFICATA / CERTIFIED
EN 14450-S2



CASSETTE IGNIFUGHE FIRE PROOF BOXES



Fire resistance tested and certified test UL 72 class 350 (Underwriter's Laboratories Inc.).





40 S NGS

Chiave a Doppia Mappa

- Alta protezione contro il fuoco: resistenza da 60 min. a 120 min., secondo il modello, in condizioni di esposizione al fuoco ad una temperatura di 1010°C.
- Serratura ad alta sicurezza certificata EN 1300, con chiave femmina a doppia mappa.
- Catenacci fissi sulla porta (lato cerniere), che impediscono lo smontaggio della stessa in caso di tentativo d'apertura tramite forzatura delle cerniere e con funzione "antistrappo".
- Il modello 635 NGS è dotato di ripiani predisposti a sostenere le cartelle sospese.
- I modelli 20 S NGS, 30 S NGS, 40 S NGS, sono dotati di 2 fori di fissaggio sulla base.
- I modelli 50 NGS e 80 NGS sono dotati di piedini in gomma e di 2 fori di fissaggio sullo schienale.
- I modelli 150 NGS, 355 NGS e 635 NGS sono dotati di ruote e profili copriruote. Per il fissaggio sono previsti 2 fori sullo schienale.

Double-Bitted Key

- High fire protection : from 60 min. up to 120 min. fire resistance, depending on the model, at a constant temperature of 1010°C.
- Lock controlled by a high security lock with double-bitted key, EN 1300 certified.
- Fixed bolts on the door (on the hinge side), to prevent any attempts to dismantle the door itself, by forcing the hinges.
- Model 635 NGS is equipped with shelves predisposed for file hanger.
- Mod. 20S NGS, 30S NGS, 40S NGS are equipped with 2 fixing holes on the bottom.
- Mod. 50 NGS and 80 NGS are equipped with rubber feet stands and 2 fixing holes on the back.
- Mod. 150 NGS, 355 NGS, 635 NGS are equipped with 4 wheels, metal wheel covers and 2 fixing holes on the back.



Art Code	Misure esterne mm. External dim. mm.			Misure interne mm. Internal dim. mm.			Resistenza al fuoco Fire Resistance	Ripiani Shelves	Cassetti Drawer	Peso Weight	Litri Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Minuti/Min	N°	N°	Kg	Lt
20 S NGS	352	412	363	260	320	234	60	0	1	31	19
30 S NGS	414	352	433	320	260	304	60	1	1	36	25
40 S NGS	514	404	440	410	300	300	60	1	1	53	37
50 NGS	546	450	460	430	350	328	60	1	1	64	49
80 NGS	832	520	520	676	380	330	90	1	1	122	85
150 NGS	1220	655	560	980	475	350	120	2	1	228	162
355 NGS	1690	775	650	1450	595	440	120	3	1	388	379
635 NGS*	1745	1116	700	1505	946	490	120	3	2	548	690

* Versione con 2 ante

* Version with double door

*iva esclusa